


# TSV



- 1 - Conductor: flexible Nickel
- 2 - P.T.F.E. tape
- 3 - Electroglass spiral impregnated with silicone rubber
- 4 - Electroglass braid impregnated with silicone rubber

**CHARACTERISTICS:**

Operating temperature of insulation materials: -40°C to +300°C

Operating voltage: 300/500 V

Test voltage: 1000 Vac for 1 minute

DESCRIPTION	CONDUCTORS CONSTRUCTION Nickel n° strands x wire ø mm	EXTERNAL DIAMETER	
		MIN. mm	MAX. mm
1x0,25 mm <sup>2</sup>	8x0,20	1,70	2,10
1x0,35 mm <sup>2</sup>	11x0,20	1,80	2,20
1x0,35 mm <sup>2</sup>	11x0,20	1,80	2,20
1x0,35 mm <sup>2</sup>	11x0,20	1,80	2,20
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,5 mm <sup>2</sup>	16x0,20	1,90	2,30
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,00	2,40
1x0,75 mm <sup>2</sup>	24x0,20	2,10	2,50
1x1 mm <sup>2</sup>	32x0,20	2,30	2,70
1x1 mm <sup>2</sup>	32x0,20	2,30	2,70
1x1 mm <sup>2</sup>	32x0,20	2,30	2,70
1x1 mm <sup>2</sup>	32x0,20	2,30	2,70
1x1 mm <sup>2</sup>	32x0,20	2,40	2,80
1x1 mm <sup>2</sup>	32x0,20	2,30	2,70