




CARTRIDGE HEATER
WITH 2 EQUAL AND INDEPENDENT SECTIONS
AND 90° TERMINAL BLOCK

XLS2I-C



Cartridge heater model XLS2I-C, with two equal and independent heating zones, with 90° cable exit, equipped with a cable outlet block. The body can be manufactured using different types of stainless steel, according to the application. Two + two wires exit from a single side and may have the same color, with numeric identification of the zones, or different colors for each zone. All heaters are equipped with an additional silicone sleeve, approximately 80 mm in length, with a diameter suitable for the power cable, to protect the cable outlet from the heater. Sealing is defined according to the application and the characteristics of the heater.

SEE BLOCK CAHRT
PAGE 115

CHART 3A

XLS2I-C - [A] - [B] - [C] - w - T - C - [G] - [H] - []

A	DIAMETER		
A	12,5 mm		
B	16 mm		
C	20 mm		
D	1/2"		
X	OTHER _____		

			H
SHEATH MODEL (see page 121)			
S	standard single insulation 80 mm		
U	single silicone sheath **		
G	metal sheath **		
C	metal braid **		
X	OTHER _____		

			G
GROUND *			
A	with ground wire (only for ø 16 mm and ø 20 mm)		
X	without ground wire		

			F
OPERATING TEMPERATURE OF THE CABLE			
	°C _____		

			E
CABLE LENGTH			
	mm _____		

B	LENGTH - L		
M	mm _____		
I	in _____		

C	Vac		
A	24		
B	110		
C	220		
D	230		
E	400		
X	OTHER _____		

D	HEATER Watt		
	watt _____		

* Of the same length as the cables

** The sheath length is always considered to be 100 mm shorter than the total cable length. The sheath diameter is defined by the manufacturer based on the resistor's specifications.