Vietata la riproduzione - Disegni e contenuti di proprietà esclusiva Mit.D. Srl

CARTRIDGE HEATER
WITH 2 DIFFERENTIATED ZONES

XLZ2-A



Cartridge Heater Model XLZ2-A, c**onsisting of a single section with 2 differentiated zones.** The body can be manufactured from various types of steel, depending on the application. Two cables exit from the same side. All heaters are equipped with an additional silicone sleeve approximately 80 mm long, with a diameter suitable for the power cables, to protect the cable exit area from the heater. Sealing is defined according to the application and the specific characteristics of the heater.

XLZ2-A	-	A	-	B	-	C	-	D Z1	-	D Z2	-	E T	-	F C	-	G	-	H	-	I

A	DIAMETER		
A	6,5 mm	G	1/4 in
B	8 mm	H	3/8 in
C	10 mm		
D	12,5 mm	I	1/2 in
E	16 mm	L	5/8 in
F	20 mm		
X	OTHER _ _ _ _		

B	LENGTH - L
M	mm _ _ _ _
I	in _ _ _ _

C	Vac
A	24
B	110
C	220
D	230
E	400
X	OTHER _ _ _ _

D	Watt per ZONE LENGTH in mm	
Z1	W _ _ _ _	mm _ _ _ _
Z2	W _ _ _ _	mm _ _ _ _

I	SHEATH MODEL (see page 121)
S	standard single insulation 80
U	single silicone sheath ***
G	metal sheath ***
C	metal braid ***
D	single silicone sheath + outer silicone sheath ***
M	metal sheath + outer metal sheath ***
Z	metal braid + outermetal braid ***
X	OTHER _ _ _ _

H	THERMOCOUPLE *
X	without thermocouple
A	TCJ bottom side
B	Central TCJ
C	TC K bottom side
D	Central TC K
E	PT100 bottom side **
F	Central PT100 **

G	GROUND *
A	with ground wire (only for ø 16 mm and ø 20 mm)
X	without ground wire

F	OPERATING TEMPERATURE OF THE CABLE
	°C _ _ _ _

E	CABLE LENGTH
mm	_ _ _ _

* Of the same length as the cable.

** According to the heater's specifications

*** The length of the silicone sleeves is always intended to be 100 mm less than the total cable length. The diameter of the sleeves is defined by the manufacturer based on the characteristics of the heater.